

# GLOSSARY OF TERMS

---



## APPENDIX

# A

### TABLE OF CONTENTS

*Glossary of Terms* . . . . . A-2

## GLOSSARY OF TERMS

### **AXIAL MOVEMENT**

Often called “endplay.” The endwise movement of motor or gear shafts. Usually expressed in thousandths of an inch.

### **BACK DRIVING**

Driving the output shaft of a gearbox to increase speed rather than reduce speed. Shaft Mount gearboxes are not suitable for service to increase speed.

### **BACKLASH**

Rotational movement of the output shaft clockwise and counter clockwise, while holding the input shaft stationary. Usually expressed in thousandths of an inch and measured at a specific radius at the output shaft.

### **BACKSTOP**

In applications where it is possible for the load to drive the gearbox in reverse when the motor is off (such as an inclined conveyor belt), a backstop should be installed to prevent the gearbox from turning in reverse.

### **CENTER DISTANCE**

A basic measurement or size reference for worm gearboxes. The distance between the centerlines of the input and output shafts.

### **EFFICIENCY**

A ratio of the input power compared to the output power, usually expressed as a percentage.

### **FLANGED REDUCER**

Usually used to refer to a gearbox having provisions for close coupling of a motor either via a hollow (quill) shaft or flexible coupling. Most often a NEMA C-face motor is used.

### **GEARBOX**

Also called a Speed Reducer. An enclosed set of gears used in mechanical power transmission to reduce speed and increase torque.

### **INPUT POWER**

The power applied to the input shaft of a gearbox. There are separate ratings for Mechanical Input Power, Thermal Input Power, and Nominal Motor Horsepower.

### **K FACTOR**

Also called an Overhung Load Factor. A constant used to modify the overhung load rating of a gearbox based on the type of load applied on the shaft. Use the K factor either to increase the calculated overhung load, or to reduce the gearbox overhung load rating.

### **MECHANICAL RATINGS**

The maximum power or torque a gearbox can transmit based on the strength and durability of its components. Some applications require the gearbox Mechanical Ratings to be reduced by a Service Factor.

### **MOUNTING POSITION**

The relationship of the input and output shafts of a gearbox relative to horizontal.

### **NOMINAL MOTOR HORSEPOWER**

The highest horsepower 1800 rpm motor that can be used with the gearbox under 1.0 service factor conditions. This rating decreases as the motor speed decreases, and as the service factor increases.

### **OUTPUT HORSEPOWER**

The amount of horsepower available at the output shaft of a gearbox. Output horsepower is always less than the input horsepower due to the efficiency of the gearbox.

**OVERHUNG LOAD**

A force applied at right angles to a shaft beyond its outermost bearing. This shaft-bending load must be supported by the bearing. Overhung load ratings are listed for each gearbox size, and should not be exceeded. Some applications require the gearbox Overhung Load rating to be reduced by a K Factor and/or a Service Factor.

**OVERHUNG LOAD FACTOR**

K Factor.

**PRIME MOVER**

In industry, the prime mover is most often an electric motor. Occasionally engines, hydraulic or air motors are used. Special considerations are called for when other than an electric motor is the prime mover.

**SELF-LOCKING**

The inability of a reducer to be driven backwards by its load. *No IronHorse gearbox should be considered self-locking.*

**SERVICE CLASS**

The American Gear Manufacturers Association (AGMA) standard 6009 lists many applications by a service class (I, II, III) with class I being the simplest applications and class III being the most complex. These applications are directly associated with specific service factor ranges (refer to the Service Factor table on [page 2-2](#)).

**SERVICE FACTOR (FOR GEARBOX)**

A constant used to modify the Mechanical Rating of a gearbox based on the duration of service and characteristics of the driven load. Use the Service Factor either as a multiplier to increase the calculated loads, or as a divisor to reduce the gearbox Mechanical and Overhung Load ratings (refer to the Service Factor table on [page 2-2](#)).

**SERVICE FACTOR (FOR MOTORS)**

Refers to a motor's ability to handle a load greater than the motor's rated horsepower on a continuous basis.

**SPEED REDUCER**

Gearbox.

**THERMAL RATINGS**

The power or torque a gearbox can transmit continuously. These ratings are based upon the cast-iron gearbox's ability to dissipate the heat caused by friction. (Not applicable for aluminum-frame gearboxes, due to their inherently better ability to dissipate heat.)

**THRUST LOAD**

Forces along the axis of the output shaft, usually encountered in vertical-drive applications.

**BLANK  
PAGE**